



1024F ORAS SAFIRA KITCHEN FAUCET FOR SUMMER HOUSE

VALID FROM 4/2026

SINGLE-LEVER, LOW PRESSURE

EAN: 6414150110306 static.oras.com/1024F

Kitchen faucet for summer house and water heater. Swivel spout and aerator. Spout's swing angle is factory preset at 100° (can be limited to 40°– 80°). Maximum flow-rate 5 l/min. Due to the heating of water, water dripping from the aerator is a feature of this product and should not be prevented. The aerator may not be changed or supplemented with additional components. Plug in, unpressurized water heater, 5 l. Easy to install. Range of use +35° – 85°C (recommendation +65°C). In order to prevent frost damage, the faucet and the water heater must be emptied. This water heater is only allowed to operate with the original Oras summer house faucet. Warning! Water heater can heat the water up to +85°C. Beware of the instant scalding hot water from the faucet. The faucet and the water heater should not be installed separately.



- Deck mounted
- Chrome
- Swivel spout, Swivel range limiting option, Profile construction
- Standard aerator
- Single operating lever/handle, Hot/Cold symbols
- Water heater unit
- Limitation option for maximum temperature and flow-rate
- ø 40 mm ceramic cartridge for flow and temperature control
- Flexible inlet pipes
- 3S-installation system for safe and simple mounting

TECHNICAL DATA

FLOW PROPERTIES

Flow-rate at 300 kPa (with flow controller)	0.072 l/s
Pressure loss with flow (0.1 l/s)	580 kPa

TECHNICAL PROPERTIES

Hot water supply	max. +70°C
Working pressure	50 - 1000 kPa
Connection size	G3/8
Projection	178 mm
Backflow prevention (EN1717)	AA
Material	Brass

REGULATIONS

EN standard	EN 817
Noise class	I (ISO 3822)

APPROVALS AND DECLARATIONS

Declaration of conformity	DoC
---------------------------	-----

