2839F Oras Cubista Kitchen faucet with dishwasher valve, 6 V

Discontinued

EAN: 6414150059421
static.oras.com/2839F





Kitchen faucet with high spout. Swivel spout, aerator and electronic dishwasher valve. Spout's swing angle is factory preset at 120° (can be limited to 0° or 60°).


Dishwasher valve closes automatically after 4 or 12 hours (one push opens the valve for 4 hours, pushing for 5 seconds opens the valve for 12 hours). Battery operated, 6 V.

F = with flexible pipes

- Kitchen
- Single-lever, Battery-operated, Dishwasher valve
- Deck mounted
- Chrome
- Swivel spout, Swivel range limiting option
- Standard aerator
- Electronic stop valve for external equipment
- Single operating lever/handle, Hot/Cold symbols
- Limitation option for maximum temperature and flow-rate
- Litter filter(s), ø 40 mm ceramic cartridge for flow and temperature control
- Solenoid valve, Light indicated function(s), Low battery indicator
- Flexible inlet pipes








© 2024 Oras Ltd. - www.oras.com - 19.03.2024

Technical data

Flow properties

Flow-rate at 300 kPa	**0.2 l/s**
Pressure loss with flow (0.2 l/s)	**300 kPa**



Technical properties

Hot water supply	**max. +70°C**
Working pressure	**100 - 1000 kPa**
Connection size	**G3/8**
Projection	**205 mm**
Backflow prevention (EN1717)	**AA**
Material	**Brass**

Software settings

Dishwasher valve open period	**4 h / 12 h**

Electronic properties

Battery	**Lithium 2CR5 6 V**

Regulations


EU Directives	**CE EMC Directive 2014/30/EU , RoHS Directive 2011/65/EU**
EN standard	**EN 15091 , EN 817, ETSI EN 301 489-1 V1.9.2 , ETSI EN 300 328 v2.2.2 , EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011+AC:2012 , EN 60335-1:2012+A11+A13+A1+A14+A2+A15:2021, Part 19.11.4**
Noise class	**I (ISO 3822)**
Protection class	**IP 55**

Approvals and Declarations

STF certificate	**EUFI29-22005212-TH**
KIWA SE	**1565**
UN38.3	**UN38-3 Maxell 2CR5**

© 2024 Oras Ltd. - www.oras.com - 19.03.2024

Spare parts



SP2839F

	Name	Code
01	Fixing plates with nuts	158697
02	Tightening nut	158726
03	Fixing screw, M6x65	158747/10
04	Supporting plate, 100x60mm	158825
05	Cartridge	158890
06	Extension screw kit, M6	158893
07	Spout	159010V
08	Lever	159050V
09	Covering cap	159053V
10	Sealing kit	159499
11	Aerator, M22x1 HC B	232201
12	Spout overturning stopper, 120°	159670/10
13	Spout overturning stopper, 60°/0°	159667V
13	Spout overturning stopper, 60°/0°	159667/10
14	Solenoid valve	600047V
15	Litter filter	600038V
16	Battery casing, 2CR5 6 V	199417V
17	Lithium battery, 2CR5 6 V	198330
18	Cap	600093V

© 2024 Oras Ltd. - www.oras.com - 19.03.2024