



Oras Aurelia A Harmony of Simplicity and Elegance.

The design of Oras Aurelia is characterized by pure, fluid shapes—timeless in their simplicity yet subtly complex in execution. This results in a delicate dance between the straightforward and the intricate, visually capturing nature's own balance.

Stand beneath the cascading water to experience a symphony of sensations, as clever design ensures efficient water distribution, embracing the complete body in refreshing and rejuvenating comfort.

Elevate your daily ritual with Oras Aurelia, where every drop becomes a celebration of inherent beauty.

1-spray, 250x250 overhead shower  
1-spray stick hand shower  
1750mm hose

## ELEVATING YOUR MOMENTS

- Wall mounted
- Chrome
- Temperature control handle, Flow control handle, Hot/Cold symbols, Eco feature for water flow
- Hand shower, Swivel overhead shower, Lockable in the middle position, Rotatable ball joint connection, Shower rail, Variable fixing points, Adjustable shower rail bracket, Anti limescale technology (easy to clean), Shower hose (1750 mm), Twist guard for shower hose
- Normal - Even and soft water stream
- Safety stop against scalding at 38°C, The housing of the fittings conducts minimal heat
- Ceramic head part for flow control, Thermostatic cartridge for automatic temperature control, Non-return valve(s), Litter filter(s)
- Direct connection, Internal thread, Cover plate(s)
- Flexible length / can be shortened, Anti-twist hose connector
- 1 spray function

## TECHNICAL DATA

### FLOW PROPERTIES

Eco-flow at 300 kPa	0.12 l/s
Flow-rate at 300 kPa	0.13 l/s
Pressure loss with flow (0.2 l/s)	200 kPa

### TECHNICAL PROPERTIES

Hot water supply	max. +65°C
Working pressure	100 - 1000 kPa
Connection size	G3/4
Installation width	150 ± 3 mm
Backflow prevention (EN1717)	EB
Material	Brass/Composite

### REGULATIONS

EN standard	EN 1111, EN 1112, EN 1113
Noise class	I (ISO 3822)

### APPROVALS AND DECLARATIONS

Declaration of conformity	DoC
EPD	S-P-07819

### SUSTAINABILITY

EPD module A1-A3 (kg CO2 eq.)	23,15
EPD module A4 (kg CO2 eq.)	0,61
EPD module B7 (kg CO2 eq.)	1389,60
EPD module C2 (kg CO2 eq.)	0,04
EPD module C3 (kg CO2 eq.)	0,04
EPD module C4 (kg CO2 eq.)	1,27
EPD module D (kg CO2 eq.)	-15,13

