



# 7151N ORAS OPTIMA STYLE SHOWER FAUCET, 40CC

THERMOSTATIC

EAN: 6414150099434 [static.oras.com/7151N](http://static.oras.com/7151N)

Designed to impress and give an elegant solution for any bathroom.

This thermostat gives you a most comfortable and enjoyable shower experience every day. With focus on high performance while still have an eye on the aesthetics and details to secure an elegant installation. The handles are designed to be elegant while still providing a good grip for easy.

Elegant design and total enjoyment

- Wall mounted
- Chrome
- Standard aerator
- Temperature control handle, Flow control handle, Hot/Cold symbols, Easy-Grip surface, Eco feature for water flow
- Safety stop against scalding at 38°C, The housing of the fittings conducts minimal heat
- Ceramic head part for flow control, Thermostatic cartridge for automatic temperature control, Non-return valve(s), Litter filter(s)
- Direct connection, Internal thread
- Inner body made of DZR brass
- Without couplings

## TECHNICAL DATA

### FLOW PROPERTIES

Eco-flow at 300 kPa	0.12 l/s
Flow-rate at 300 kPa	0.22 l/s
Pressure loss with flow (0.2 l/s)	250 kPa

### TECHNICAL PROPERTIES

Hot water supply	max. +80°C
Working pressure	100 - 1000 kPa
Connection size	G1/2
Installation width	40 mm
Backflow prevention (EN1717)	EB
Material	Brass/Composite

### REGULATIONS

EN standard	EN1111
Noise class	I (ISO 3822)

### APPROVALS AND DECLARATIONS

Declaration of conformity	DoC
EPD	S-P-06397

### SUSTAINABILITY

EPD module A1-A3 (kg CO2 eq.)	14,28
EPD module A4 (kg CO2 eq.)	0,51
EPD module B7 (kg CO2 eq.)	1266,00
EPD module C2 (kg CO2 eq.)	0,02
EPD module C3 (kg CO2 eq.)	0,03
EPD module C4 (kg CO2 eq.)	1,02
EPD module D (kg CO2 eq.)	-9,06

