



# 7422G-33 ORAS NOVA ECO SHOWER FAUCET WITH SHOWER SET, 160CC

THERMOSTATIC

EAN: 6414150103278 [static.oras.com/7422G-33](http://static.oras.com/7422G-33)



- Wall mounted
- Matt black
- Temperature control handle, Flow control handle, Eco feature for water flow
- Hand shower, Shower rail, Adjustable shower rail bracket, Soap dish, Shower hose (1500 mm), Eco flow control
- ECO - Water saving stream
- Limitation option for maximum temperature and flow-rate, Safety stop against scalding at 38°C
- Ceramic head part for flow control, Thermostatic cartridge for automatic temperature control, Non-return valve(s), Litter filter(s)
- Direct connection, Internal thread
- 1 spray function

## TECHNICAL DATA

### FLOW PROPERTIES

Flow-rate at 300 kPa (with flow controller) **0.12 l/s**

### TECHNICAL PROPERTIES

DN-size (nominal dimension) **DN15**  
Hot water supply **max. +80°C**  
Working pressure **100 - 1000 kPa**  
Connection size **M26x1.5**  
Installation width **160 mm**  
Backflow prevention (EN1717) **EB**  
Material **Brass**

### REGULATIONS

EN standard **EN 1111, EN 1112, EN 1113**  
Noise class **I (ISO 3822) Oras lab.**

### APPROVALS AND DECLARATIONS

Declaration of conformity **DoC**  
EPD **S-P-07819**

### SUSTAINABILITY

EPD module A1-A3 (kg CO2 eq.) **14,00**  
EPD module A4 (kg CO2 eq.) **0,37**  
EPD module B7 (kg CO2 eq.) **1389,60**  
EPD module C2 (kg CO2 eq.) **0,03**  
EPD module C3 (kg CO2 eq.) **0,03**  
EPD module C4 (kg CO2 eq.) **0,77**  
EPD module D (kg CO2 eq.) **-9,15**

